


Union Special LEWIS . COLUMBIA

INDUSTRIAI SEWING MACHINES

STYLE 39500X



CLASS 39500

No.

STREAMLINED
HIGH SPEED OVERSEAMERS

Union Special MACHINE COMPANY

CHICAGO

From the library of: Superior Sewing Machine & Supply LLC

Catalog No. 103 X (Supplement to Catalog No. 103 R)

INSTRUCTIONS

FOR

ADJUSTING AND OPERATING

LIST OF PARTS

CLASS 39500

Style

39500 X

The parts listed in this catalog are furnished at list prices for repairs only.

First Edition

Copyright 1959
by
Union Special Machine Co.
Rights Reserved in All Countries



Printed in U.S.A.

FOREWORD

The Class 39500 machine is Union Special's latest overedger. New streamlined styling, automatic lubrication, and light running high speed performance are characteristics of these machines. All parts are made by precision methods insuring complete interchangeability.

It is our constant aim to furnish carefully prepared information that will enable the customer to secure all possible advantages from the use of Union Specials. The following pages contain valuable operating and adjusting data, and illustrate and describe the parts for Styles in Class 39500.

Union Special representatives will be found in all manufacturing centers, anxious to cooperate with you to plan and estimate requirements.

Union Special MACHINE COMPANY

Engineering Department

IDENTIFICATION OF MACHINE

Each Union Special carries a Style number which is stamped in the name plate on the machine. Style numbers are classified as standard and special. Standard Style numbers have one or more letters suffixed, but never contain the letter "Z". Example: "Style 39500 X". Special Style numbers contain the letter "Z". When only minor changes are made in a standard machine, a "Z" is suffixed to the standard Style number. Example: "Style 39500 XZ".

Styles of machines similar in construction are grouped under a Class number, which contains no letters. Example: "Class 39500".

APPLICATION OF CATALOG

This catalog is a supplement to Catalog No. 103 R and should be used in conjunction therewith. Only those parts which are used on Style 39500 X and not on Style 39500 N are illustrated and listed at the back of the book.

This catalog applies specifically to the standard Styles of machines as listed herein. It can also be applied with discretion to some special machines in Class 39500. All references to directions, such as right and left, front and back, etc., are taken from the operator's position while seated at the machine. Operating direction of handwheel is away from operator.

STYLES OF MACHINES

Single Curved Blade Needle, Two Looper, Three Thread, Overseaming Machine. Plain Feed, Trimming Mechanism with Spring Pressed Lower Knife, Automatic Lubricating System.

39500 X For simultaneously attaching right pants flies and zipper tapes to pants fronts; also attaching zippers to right flies only and similar operations. Seam specification 504-SSa-1 or 504-SSj-1, standard seam width 3/8 inch; stitch range 6 to 16 per inch, standard setting 10 per inch.

OILING

CAUTION! Oil was drained from machine when shipped, so reservoir must be filled before beginning to operate. Oil capacity of Class 39500 is six ounces. A straight mineral oil of a Saybolt viscosity of 200 to 250 seconds at 100° Fahrenheit should be used.

Machine is filled with oil at spring cap in top cover. Oil level is checked at sight gauge on front of machine. Red bulb on oil level indicator should show between gauge lines.

Machine is automatically lubricated. No oiling is necessary, other than keeping main reservoir filled. Check oil daily before the morning start; add oil as required.

Drain plug screw is located at back of machine near bottom edge of base. It is a magnetic screw designed to accumulate possible foreign materials which may have entered the crank case. It should be removed and cleaned periodically.

NEEDLES

Each Union Special needle has both a type and size number. The type number denotes the kind of shank, point, length, groove, finish and other details. The size number, stamped on the needle shank, denotes largest diameter of blade, measured in thousandths of an inch, midway between the shank and the eye. Collectively, the type and size number represent the complete symbol which is given on the label of all needles packaged and sold by Union Special.

Style 39500 X uses curved blade needles. The standard needle for this style is Type 154 GAS. It is a curved blade, standard length, single groove, shallow spot, long tapered point, struck groove, chromium plated needle and is available in sizes 022, 025, 027, 029, 032, 036, 040, 044, 049, and 054.

To have needle orders promptly and accurately filled, an empty package, a sample needle, or the type and size number should be forwarded. Use the description on label. A complete order would read: "1000 Needles, Type 154 GAS, Size 036".

Selection of proper needle size is determined by the size of thread used. Thread should pass freely through the needle eye in order to produce a good stitch formation.

Success in the operation of Union Special machines can be secured only by use of needles packaged under our brand name, *Union Special*, which is backed by a reputation for producing highest quality needles in materials and workmanship for more than three-quarters of a century.


CHANGING NEEDLES, ETC.

All instructions in regard to Changing Needles, Thread Stand, Threading, are the same as for Style 39500 N covered in Catalog No. 103 R.

ASSEMBLING AND ADJUSTING SEWING PARTS

All the instructions pertaining to the adjustment of Style 39500 X are the same as those for Style 39500 N illustrated in Catalog No. 103 R except for the following:

- 1. Under the heading "SETTING THE NEEDLE", the height of the needle above the throat plate for Style 39500 X should be 15/32 inch instead of 1/2 inch.
- 2. Under the same heading, in paragraph three, the looper gauge for Style 39500 X should be 3/32 inch instead of 1/8 inch, and looper gauge No. 21225-3/32 should be used.



The parts illustrated on the preceding page and described on this page represent the parts that are used on Style 39500 X, but not used on Style 39500 N.

Those parts shown in phantom views and bearing no reference numbers are common to Styles $39500~\mathrm{X}$ and $39500~\mathrm{N}_{\bullet}$

Use Catalog No. 103 R for all parts not illustrated or described here.

Ref.	Part		Amt.
No.	No.	Description	Req.
1	39556 D	Presser Foot Arm	1
$\frac{1}{2}$	39578 BA	Chip Guard	
3	39520 X	Presser Foot	ī
4	87 U	Screw	
5	39530	Hinge Spring	
6	28	Screw	
7	39530 J	Guide, marked "A"	1
8	39556 M	Chain Cutting Knife, complete	
9	22798	Screw	· 1
10	39556 L	Chain Cutting Knife	1
11	605	Screw	2
12	39570 J	Upper Knife	
13	39550 R	Lower Knife Holder Locating Stud	. 1
14	39549 J	Lower Knife	. 1
15	39550 P	Knife Holder Spring	1
16	39524 X	Throat Plate, marked "AR"	· 1
17	39540 B -1 0	Main Feed Driving Eccentric, .022 inch throw	1
18	39505 X	Main Feed Dog	· 1
19	39505 M	Chaining Feed Dog, marked "Y"	· 1
20	39503 A	Edge Guide, adjustable	· 1
21	39503 D	Edge Guide Swinging Arm	. 1
22	604	Screw	· 2
23	12957 E	Washer	• 1
24	22758 E	Screw	1
25	39503 C	Edge Guide Mounting Bracket	. 1
26	22569 C	Screw	· 2
27	39578 S	Fabric Guard	1





UNION SPECIAL maintains sales and service facilities throughout the world. These offices will aid you in the selection of the right sewing equipment for your particular operation. Union Special representatives and service men are factory trained and are able to serve your needs promptly and efficiently. Whatever your location, there is a Union Special Representative to serve you. Check with him today.

ATLANTA, GA.

BOSTON, MASS.

CHICAGO, ILL.

DALLAS, TEXAS

LOS ANGELES, CAL.

NEW YORK, N. Y.

PHILADELPHIA, PA.

MONTREAL, QUEBEC

BRUSSELS, BELGIUM

LEICESTER, ENGLAND

LONDON, ENGLAND

PARIS, FRANCE

STUTTGART, GERMANY

Representatives and distributors in all important industrial cities throughout the world.



MACHINE COMPANY

400 N. FRANKLIN ST., CHICAGO, ILL. 60610